

## FICHA TECNICA COMBIS

### FS 10 (One part)

| Part | Length<br>Plate | Clamp Length          | Range   |         |
|------|-----------------|-----------------------|---------|---------|
|      |                 |                       | Min. Od | Max. Od |
| A    | 317             | 300 / 400 / 500 / 600 | 91      | 98      |
| B    | 383             | 300 / 400 / 500 / 600 | 111     | 121     |
| C    | 446             | 300 / 400 / 500 / 600 | 131     | 141     |
| D    | 543             | 300 / 400 / 500 / 600 | 162     | 172     |
| E    | 637             | 300 / 400 / 500 / 600 | 193     | 203     |

### FS 20 (Two parts)

| Part | Combined<br>With | Length<br>Plate | Clamp Length          | Range   |         |
|------|------------------|-----------------|-----------------------|---------|---------|
|      |                  |                 |                       | Min. Od | Max. Od |
| A    | B                | 700             | 300 / 400 / 500 / 600 | 213     | 233     |
|      | C                | 763             | 300 / 400 / 500 / 600 | 233     | 253     |
|      | D                | 860             | 300 / 400 / 500 / 600 | 264     | 284     |
|      | E                | 954             | 300 / 400 / 500 / 600 | 295     | 315     |
| B    | C                | 829             | 300 / 400 / 500 / 600 | 253     | 273     |
|      | D                | 926             | 300 / 400 / 500 / 600 | 284     | 304     |
|      | E                | 1020            | 300 / 400 / 500 / 600 | 314     | 334     |
| C    | D                | 989             | 300 / 400 / 500 / 600 | 304     | 324     |
|      | E                | 1083            | 300 / 400 / 500 / 600 | 335     | 355     |
| D    | E                | 1180            | 300 / 400 / 500 / 600 | 366     | 386     |

### FS 30 (Three parts)

| Part | Combined<br>With | Length<br>Plate | Clamp Length          | Range   |         |
|------|------------------|-----------------|-----------------------|---------|---------|
|      |                  |                 |                       | Min. Od | Max. Od |
| A    | B and C          | 1146            | 300 / 400 / 500 / 600 | 354     | 384     |
|      | B and D          | 1243            | 300 / 400 / 500 / 600 | 386     | 416     |
|      | B and E          | 1337            | 300 / 400 / 500 / 600 | 416     | 446     |
|      | C and D          | 1306            | 300 / 400 / 500 / 600 | 406     | 436     |
|      | C and E          | 1400            | 300 / 400 / 500 / 600 | 436     | 466     |
| B    | D and E          | 1497            | 300 / 400 / 500 / 600 | 467     | 497     |
|      | C and D          | 1372            | 300 / 400 / 500 / 600 | 426     | 456     |
|      | C and E          | 1466            | 300 / 400 / 500 / 600 | 456     | 486     |
| C    | D and E          | 1563            | 300 / 400 / 500 / 600 | 487     | 517     |
|      | D and E          | 1626            | 300 / 400 / 500 / 600 | 508     | 538     |

### FS 40 (Four parts)

| Part | Combined<br>With | Length<br>Plate | Clamp Length          | Range   |         |
|------|------------------|-----------------|-----------------------|---------|---------|
|      |                  |                 |                       | Min. Od | Max. Od |
| A    | B,C and D        | 1689            | 300 / 400 / 500 / 600 | 527     | 567     |
|      | B,C and E        | 1783            | 300 / 400 / 500 / 600 | 558     | 598     |
|      | B,D and E        | 1880            | 300 / 400 / 500 / 600 | 589     | 629     |
| C    | D,E and A        | 1943            | 300 / 400 / 500 / 600 | 609     | 649     |
| B    | C,D and E        | 2009            | 300 / 400 / 500 / 600 | 629     | 669     |

### FS 50 (Five Parts)

| Part | Combined<br>With | Length<br>Plate | Clamp Length          | Range   |         |
|------|------------------|-----------------|-----------------------|---------|---------|
|      |                  |                 |                       | Min. Od | Max. Od |
| A    | B,C,D and E      | 2326            | 300 / 400 / 500 / 600 | 730     | 780     |